1982 Subject and Author Index

All of the articles in the 1982 Forest Products Journal, Volume 32, are listed both by subject and by author. The Subject Index is organized according to the FPRS Division and Technical Committee structure.

The Author Index lists senior author entries which give complete information for the article, and coauthor entries which refer back to the senior author.

Reprints of most articles are available at $2 each, minimum $5, plus 10 percent shipping and handling. Bulk rates are also available. When ordering, please give reprint numbers. A check or money order must accompany each order.

FUNDAMENTAL DISCIPLINES DIVISION

Biology

Bulk Densities of Materials From Selected Pine-Site Hardwoods, C.G. Vidrine and G.E. Woodson, 7:21-24 (No. 6245).

Changes in Aspen Bark Stored in Outdoor Piles, L.L. Zoch, Jr., J.J. Rusch, and E.L. Springer, 6:31-34 (No. 6376).

Cultivation of Shiitake, the Japanese Forest Mushroom, on Logs: A Potential Industry for the United States, G.F. Leatham, 8:29-35 (No. 6350).

Methyl Bromide Treatment of Oak Wilt Infected Logs: Laboratory and Preliminary Field Fumigations, E.L. Schmidt, M.M. Ruetze, and D.W. French, 3:46-49 (No. 6257).

Mold and Sapstain Control: Laboratory and Field Tests of 44 Fungicidal Formulations, A.J. Cserjesi and E.L. Johnson, 10:59-68 (No. 6354).

Wood Lath Filters in Waste-Water Treatment Plants, D.J. Miller, 2:41-44 (No. 6276).

Chemistry

Double Application of Paraquat for Production of Lightwood With High Oleoresin Content, D.R. Roberts, I.L. Williams, and S.V. Kossuth, 10:74-78 (No. 6383).

Industrial Use of Wood-Polymer Materials: State of the Art, J.A. Meyer, 1:24-29 (No. 6321).

Physics

Dimensional Stability of Flakeboards as Affected by Board Specific Gravity and Flake Alignment, R.L. Geimer, 8:44-52 (No. 6390).

Effect of Calcium Silicate Substrate on Thermal Barrier Fire Testing, R.H. White, 7:25-27 (No. 6429).

Effect of Wood on Humidity in Homes, H. Kubler, 6:47-50 (No. 6393).

Moisture Movement and Control in Light-Frame Structures, G.E. Sherwood and A. TenWolde, 10:69-73 (No. 6448).

Response of Experimental Hardboard Dimensions and Weight to Cyclic Relative Humidity, G.C. Myers, 7:41-44 (No. 6392).

Wood Engineering & Mechanical Properties

Creep of Thick Structural Flakeboards in Constant and Cyclic Humidity, J.D. McNatt and M.O. Hunt, 5:49-54 (No. 6320).

Dimensional Stability of Flakeboards as Affected by Board Specific Gravity and Flake Alignment, R.L. Geimer, 8:44-52 (No. 6390).

Effect of Construction Variables on Performance of Wood-Stud Walls, A. Polensek, 5:37-41 (No. 6333).

Effect of Lumber Width and Tension Lamination Quality on the Bending Strength of Four-Ply Laminated Beams, C.M. Marx and R.C. Moody, 1:45-52 (No. 6254).

Examination of a Sinusoidal Joint for Assembling Wood I-Beam Components, A. Sliker and O. Suchsland, 7:16-20 (No. 6335).

Hardboard Quality When Produced in Closed White Water Systems, M.B. Jansson, 6:39-46 (No. 6309).

Influence of Paper Birch on the Properties of Aspen Waferboard: A Mill Trial, R. Gertjejansen and D. Hedquist, 11/12:33-34 (No. 6378).

Kiln-Drying Douglas-fir Pole Sections: Effects on Strength and Checking, C.J. Kozlik, 6:24-30 (No. 6353).

Longitudinal Stress Waves for Lumber Stress Grading: Factors Affecting Applications: State of the Art, C.C. Gerhards, 2:20-25 (No. 6336).

Methodology to Evaluate Racking Resistance of Nailed Walls, R.Y. Itani, R.L. Tuomi, and W.J. McCutcheon, 1:30-36 (No. 6205).

Preliminary Evaluation of the Strength and Stiffness of Yellow-poplar Pallet Shook, T.E. McLain and J.S. Holland, 11/12:51-56 (No. 6418).

Preservative Treatment Effects on Mechanical and Thickness Swelling Properties of Aspen Waferboard, H.J. Hall, R.O. Gertjejansen, E.L. Schmidt, C.G. Carll, and R.C. DeGroot, 11/12:19-26 (No. 6364).

Procedure for Calculating Distributed Load Deflection in Log Beams, R.H. Perkins, 8:41-43 (No. 6411).

Properties of Parallel-Laminated Veneer From Stress-Wave-Tested Veneers, J. Jung, 7:30-35 (No. 6380).

Properties of Particle- and Hardboard Made From Healthy and Beetle-Killed Southern Pine, M.W. Kelly, J.E. Barefoot, W.H. Swint, and M.P. Levi, 3:33-39 (No. 6291).

Response of Experimental Hardboard Dimensions and Weight to Cyclic Relative Humidity, G.C. Myers, 7:41-44 (No. 6392).

Reverse Proofloading of Lumber, L.A. Marin and F.E. Woeste, 10:53-55 (No. 6294).

Rolling Shear Properties of Southern Pine Plywood and Unidirectionally Laminated Veneer, E.J. Biblis, W.-L. Chen, and W.-C. Lee, 2:45-50 (No. 6222).

Strength of Untreated Douglas-fir Foundation Piles After Some 70 Years' Service, A.P. Schniewind, B. Gannon, and B.A. Bendtsen, 11/12:39-46 (No. 6419).

Wood-Stud Walls: Stiffness of Joints Between Studs and Hardwood Panelings, A. Polensek and K.M. Bastendorff, 7:51-53 (No. 6358).

Wood-Stud Walls: Structural Properties of Stuccoed Sheathing, A. Polensek and K.M. Bastendorff, 4:54-56 (No. 6310).

MANAGEMENT

Economics & Financial Management

Economic Analysis of the Sawmill Improvement Program, C.D. Risbrudt and H.F. Kaiser, 8:25-28 (No. 6362).

Economic Perspective on Harvesting and Physical Constraints on Utilizing Small, Dead Lodgepole Pine, P.J. Ince, 11/12:61-66 (No. 6434).

Financial Analysis of Equipment Replacement, R.A. Tufts and W.L. Mills, Jr., 10:45-52 (No. 6406).

Regional Price Variation of Southern Pine Sawtimber and Pulpwood, T.P. Hunter, 9:23-26 (No. 6412).

U.S. Wood-Based Panel Industry: Standards for Panel Products, C.G. Carll, H.E. Dickerhoof, and J.A. Youngquist, 7:12-15 (No. 6342).

Marketing

Market Potential for Wood Fuel—A Limiting Factor in Wood Energy Development, R.A. Harris, 11/12: 67-70 (No. 6394).

U.S Wood-Based Panel Industry: Production Trends and Changing Markets, H.E. Dickerhoof, J.A. Youngquist, and C.G. Carll, 6: 14-23 (No. 6341).

U.S. Wood-Based Panel Industry: Standards for Panel Products, C.G. Carll, H.E. Dickerhoof, and J.A. Youngquist, 7:12-15 (No. 6342).

Production Management

Financial Analysis of Equipment Replacement, R.A. Tufts and W.L. Mills, Jr., 10:45-52 (No. 6406).

Mathematical Model for Determining the Quantity of Materials Produced in Sawmilling, M. Savsar and P.C. Kersavage, 11/12:35-38 (No. 6458).

Selecting Precision Levels for Measurments, T.A. Max and T.A. Snellgrove, 11/12:27-28 (No. 6475).

Quality Control

Selecting Precision Levels for Measurements, T.A. Max and T.A. Snellgrove, 11/12:27-28 (No. 6475).

Research Management

Selecting Precision Levels for Measurements, T.A. Max and T.A. Snellgrove, 11/12:27-28 (No. 6475).

U.S. Wood-Based Panel Industry: Research and Technological Innovations, J.A. Youngquist, C.G. Carll, and H.E. Dickerhoof, 8:14-24 (No. 6343).

PROCESSES DIVISION

Drying & Storage

Estimating Air-Drying Moisture Content Losses for Red Oak and Yellow-poplar Lumber, J. Denig and E.M. Wengert, 2:26-31 (No. 6280).

Experimental Solar-Dehumidifier Kiln for Drying Lumber, P.Y.S. Chen, W.A. Helmer, H.N. Rosen, and D.J. Barton, 9:35-41 (No. 6395).

Kiln-Drying Douglas-fir Pole Sections: Effects on Strength and Checking, C.J. Kozlik, 6:24-30 (No. 6353).

Mechanics of Compression Drying Solid Wood Cubes and Chip Mats, J.G. Haygreen, 10:30-38 (No. 6446).

Predrying Before Press-Drying to Reduce Drying Defects in Hard-

woods, W.T. Simpson, 11/12:77-80 (No. 6428).

Principles of Dehumidification Lumber Drying, P.Y.S. Chen and W.A. Helmer, 5:24-28 (No. 6329).

Solar and Air Lumber Drying During Winter in Virginia, L.C. de S. Oliveira, C. Skaar, and E.M. Wengert, 1:37-44 (No. 6256).

Some General Characteristics of Capacitive In-Kiln Moisture Monitors, W.L. James and R.S. Boone, 4:57 (No. 6399).

Steam Recovery in a High-Temperature Lumber Dry Kiln by Steam-Jet Thermocompressor, K. Masters and S.E. Corder, 4:50-53 (No. 6139).

Using Speed of Sound in Wood to Monitor Drying in a Kiln, W.L. James, R.S. Boone, and W.L. Galligan, 9:27-34 (No. 6401).

Warp Reduction in Kiln-Drying Hardwood Dimension, W. Simpson, 5:29-32 (No. 6308).

Energy Generation & Conservation

Changes in Aspen Bark Stored in Outdoor Piles, L.L. Zoch, Jr., J.J. Rusch, and E.L. Springer, 6:31-34 (No. 6376).

Construction and Startup of a Wood Gasification Pilot Plant, A.D. Jape and T.F. McGowan, 7:45-50 (No. 6355).

Economic Feasibility of Utilizing Urban Wood: Case Study of the San Francisco Bay Area, M. Kent, J.A. Wagar, and W.A. Dost, 9:46-52 (No. 6338).

Market Potential for Wood Fuel--A Limiting Factor in Wood Energy Development, R.A. Harris, 11/12:67-70 (No. 6394).

Mechanics of Compression Drying Solid Wood Cubes and Chip Mats, J.G. Haygreen, 10:30-38 (No. 6446).

Rapid Determination of Wood Fuel Moisture Content Using a Microwave Oven for Drying, R.A. Harris, 10:56-58 (No. 6441).

Steam Recovery in a High-Temperature Lumber Dry Kiln by Steam-Jet Thermocompressor, K. Masters and S.E. Corder, 4:50-53 (No. 6139).

U.S. Wood-Based Panel Industry: Energy, Environmental Protection, and Occupational Safety and Health, C.G. Carll, J.A. Youngquist, and H.E. Dickerhoof, 9:14-22 (No. 6344).

Gluing

Bonding of Particleboard Using Hydrogen Peroxide, Lignosulfonates, and Furfuryl Alcohol: Effects of Chemical Composition of Bonding Materials, J.L. Philippou, E. Zavarin, W.E. Johns, and T. Nguyen, 5:55-61 (No. 6268).

Bonding of Particleboard Using Hydrogen Peroxide, Lignosulfonates, and Furfuryl Alcohol: The Effect of Process Parameters, J.L. Philippou, W.E. Johns, E. Zavarin, and T. Nguyen, 3:27-32 (No. 6269).

Copolymer Resins of Bark and Agricultural Residue Extracts With Phenol and Formaldehyde: 40 Percent Weight of Phenol Replacement, C.M. Chen, 11/12:14-18 (No. 6416).

Copolymer Resins of Bark and Agricultural Residue Extracts With Phenol and Formaldehyde: 20 Percent Weight of Phenol Replacement, C.M. Chen, 2:35-40 (No. 6207).

Effects of Veneer Preheating Temperature, Press and Assembly Time on Aspen LVL, P.R. Steiner and A.W. Andersen, 10:39-44 (No. 6346).

Isocyanate Bonded Aspen Flakeboard, W.E. Johns, 11/12:47-50 (No. 6372).

Urethane Bonded Particleboard, J.A. Gallagher, 4:26-33 (No. 6259).

Mechanical Fastening

Examination of a Sinusoidal Joint for Assembling Wood I-Beam Components, A. Sliker and O. Suchsland, 7:16-20 (No. 6335).

Methodology to Evaluate Racking Resistance of Nailed Walls, R.Y. Itani, R.L. Tuomi, and W.J. McCutcheon, 1:30-36 (No. 6205).

Milling & Machining

Alloy Tipping for Reduced Sawtooth Dulling, E. Kirbach and T. Bonac, 8:36-40 (No. 6295).

Dulling of Sawteeth Tipped With a Stellite and Two Cobalt-Cemented Tungsten Carbides, E. Kirbach and T. Bonac, 9:42-45 (No. 6252).

Economic Analysis of the Sawmill Improvement Program, C.D. Risbrudt and H.F. Kaiser, 8:25-28 (No. 6362).

Economics of Cutting Wood Parts With a Laser Under Optical Image Analyzer Control, H.A. Huber, C.W. McMillin, and A. Rasher, 3:16-21 (No. 6299).

Estimating Benefits From Whole-Tree Chipping as a Logging Innovation in Northern U.S. Forests, O.W. Herrick, 11/12:57-60 (No. 6449).

Estimating Sawlog Center of Gravity by Empirical Formula, R.H. Perkins, 3:50-53 (No. 6273).

4/4 Hardwood Dimension From Short Bolts: Economic and Processing Comparison of Conventional and Innovative Production, H.A. Stewart, H.N. Rosen, H.A. Huber, and A.A. Rasher, 11/12:71-76 (No. 6409).

Influence of Edging Practices on Furniture Dimension Stock Yields From Short Hardwood Lumber, M. Beaudoin, R.J. Thomas, and J.G. Schroeder, 2:53-59 (No. 6235).

Mathematical Model for Determining the Quantity of Materials Produced in Sawmilling, M. Savsar and P.C. Kersavage, 11/12:35-38 (No. 6458).

Process Control

Automation of a Laboratory Particleboard Press, R.L. Geimer, G.H. Stevens, and R.E. Kinney, 4:34-36 (No. 6382).

Economics of Cutting Wood Parts With a Laser Under Optical Image Analyzer Control, H.A. Huber, C.W. McMillin, and A. Rasher, 3:16-21 (No. 6299).

Rapid Determination of Wood Fuel Moisture Content Using a Microwave Oven for Drying, R.A.

Harris, 10:56-58 (No. 6441).

Some General Characteristics of Capacitive In-Kiln Moisture Monitors, W.L. James and R.S. Boone, 4:57 (No. 6399).

Using Speed of Sound in Wood to Monitor Drying in a Kiln, W.L. James, R.S. Boone, and W.L. Galligan, 9:27-34 (No. 6401).

Timber Production

Analytical Procedure to Locate Trees for Tree Harvest Simulators, D.P. Bradley, C.C. Hassler, and R.F. Green, 7:36-40 (No. 6356).

Bulk Densities of Materials From Selected Pine-Site Hardwoods, C.G. Vidrine and G.E. Woodson, 7:21-24 (No. 6245).

Developing Harvesting Systems for the Future: Linking Strategies, Biology, and Design, G.W. Brown, W.R. Bentley, and J.C. Gordon, 6:35-38 (No. 6384).

Economic Perspective on Harvesting and Physical Constraints on Utilizing Small, Dead Lodgepole Pine, P.J. Ince, 11/12:61-66 (No. 6434).

Ergonomic Research: Review and Needs in Southern Forest Harvesting, L.A. Smith and D.L. Sirois, 4:44-49 (No. 6345).

Estimating Benefits From Whole-Tree Chipping as a Logging Innovation in Northern U.S. Forests, O.W. Herrick, 11/12:57-60 (No. 6449).

Harvesting Systems and Costs for Southern Pine in the 1980s, F.W. Cubbage and J.E. Granskog, 4:37-43 (No. 6317).

Quantifying Logging Residue—Before the Fact, J.T. Bones, 6:51-52 (No. 6415).

PRODUCTS DIVISION

Bark & Residues

Bulk Densities of Materials From Selected Pine-Site Hardwoods, C.G. Vidrine and G.E. Woodson, 7:21-24 (No. 6245).

Changes in Aspen Bark Stored in Outdoor Piles, L.L. Zoch, Jr., J.J. Rusch, and E.L. Springer, 6:31-34 (No. 6376).

Construction and Startup of a Wood Gasification Pilot Plant, A.D. Jape and T.F. McGowan, 7:45-50 (No. 6355).

Copolymer Resins of Bark and Agricultural Residue Extracts With Phenol and Formaldehyde: 40 Percent Weight of Phenol Replacement, C.M. Chen, 11/12:14-18 (No. 6416).

Copolymer Resins of Bark and Agricultural Residue Extracts With Phenol and Formaldehyde: 20 Percent Weight of Phenol Replacement, C.M. Chen, 2:35-40 (No. 6207).

Economic Feasibility of Utilizing Urban Wood: Case Study of the San Francisco Bay Area, M. Kent, J.A. Wagar, and W.A. Dost, 9:46-52 (No. 6338).

Health Hazards Caused by Fungi in Stored Wood Chips, T. Thorngvist and H. Lundstrom, 11/12:29-32 (No. 6369).

Market Potential for Wood Fuel--A Limiting Factor in Wood Energy Development, R.A. Harris, 11/12: 67-70 (No. 6394).

Mechanics of Compression Drying Solid Wood Cubes and Chip Mats, J.G. Haygreen, 10:30-38 (No. 6446).

Quantifying Logging Residue—Before the Fact, J.T. Bones, 6:51-52 (No. 6415).

Rapid Determination of Wood Fuel Moisture Content Using a Microwave Oven for Drying, R.A. Harris, 10:56-58 (No. 6441).

Construction Plywood

Durability of CCA-B Treated Plywood Having Nonconforming Penetration Patterns, G.B. Fahlstrom, 2:51-52 (No. 6260).

Rolling Shear Properties of Southern Pine Plywood and Unidirectionally Laminated Veneer, E.J. Biblis, W.-L. Chen, and W.-C. Lee, 2:45-50 (No. 6222).

Wood-Stud Walls: Structural Properties of Stuccoed Sheathing, A. Polensek and K.M. Bastendorff, 4:54-56 (No. 6310).

Decorative Veneers & Plywood

Wood-Stud Walls: Stiffness of Joints Between Studs and Hardwood Paneling, A. Polensek and K.M. Bastendorff, 7:51-53 (No. 6358).

Furniture, Millwork, & Allied Products

Influence of Edging Practices on Furniture Dimension Stock Yields From Short Hardwood Lumber, M. Beaudoin, R.J. Thomas, and J.G. Schroeder, 2:53-59 (No. 6235).

Hardboard & Insulation Board

Formaldehyde Dynamic Air Contamination by Hardwood Plywood: Effects of Several Variables and Board Treatments, G.E. Myers, 4:20-25 (No. 6373).

Hardboard Quality When Produced in Closed White Water Systems, M.B. Jansson, 6:39-46 (No. 6309).

Properties of Particle- and Hardboard Made From Healthy and Beetle-Killed Southern Pine, M.W. Kelly, J.E. Barefoot, W.H. Swint, and M.P. Levi, 3:33-39 (No. 6291).

Response of Experimental Hardboard Dimensions and Weight to Cyclic Relative Humidity, G.C. Myers, 7:41-44 (No. 6392).

U.S. Wood-Based Panel Industry: Energy, Environmental Protection, and Occupational Safety and Health, C.G. Carll, J.A. Youngquist, and H.E. Dickerhoof, 9:14-22 (No. 6344).

U.S Wood-Based Panel Industry: Research and Technological Innovations, J.A. Youngquist, C.G. Carll, and H.E. Dickerhoof, 8:14-24 (No. 6343).

U.S Wood-Based Panel Industry: Standards for Panel Products, C.G. Carll, H.E. Dickerhoof, and J.A. Youngquist, 7:12-15 (No. 6342).

Hardwood Lumber

Estimating Sawlog Center of Gravity by Empirical Formula, R.H. Perkins, 3:50-53 (No. 6273).

4/4 Hardwood Dimension From Short Bolts: Economic and Processing Comparison of Conventional and Innovative Production, H.A. Stewart, H.N. Rosen, H.A. Huber, and A.A. Rasher, 11/12:71-76 (No. 6409).

Influence of Edging Practices on Furniture Dimension Stock Yields From Short Hardwood Lumber, M. Beaudoin, R.J. Thomas, and J.G. Schroeder, 2:53-59 (No. 6235).

Predrying Before Press-Drying to Reduce Drying Defects in Hardwoods, W.T. Simpson, 11/12: 77-80 (No. 6428).

Reverse Proofloading of Lumber, L.A. Marin and F.E. Woeste, 10: 53-55 (No. 6294).

U.S. Wood-Based Panel Industry: Production Trends and Changing Markets, H.E. Dickerhoof, J.A. Youngquist, and C.G. Carll, 6:14-23 (No. 6341).

Warp Reduction in Kiln-Drying Hardwood Dimension, W. Simpson, 5:29-32 (No. 6308).

Laminated Wood, Components, & Engineered Structures

Effect of Lumber Width and Tension Lamination Quality on the Bending Strength of Four-Ply Laminated Beams, C.M. Marx and R.C. Moody, 1:45-52 (No. 6254).

Effects of Veneer Preheating Temperature, Press and Assembly Time on Aspen LVL, P.R. Steiner and A.W. Andersen, 10:39-44 (No. 6346).

Examination of a Sinusoidal Joint for Assembling Wood I-Beam Components, A. Sliker and O. Suchsland, 7:16-20 (No. 6335).

Exposure Effects Upon Performance of Laminated Veneer Lumber and Glulam Materials, T. Laufenberg, 5:42-48 (No. 6330).

Properties of Parallel-Laminated Veneer From Stress-Wave-Tested Veneers, J. Jung, 7:30-35 (No. 6380).

Pallets & Containers

Preliminary Evaluation of the Strength and Stiffness of Yellow-poplar Pallet Shook, T.E. McLain and J.S. Holland, 11/12:51-56 (No. 6418).

Particleboard & Molded Products

Automation of a Laboratory Particleboard Press, R.L. Geimer, G.H. Stevens, and R.E. Kinney, 4:34-36 (No. 6382).

Bonding of Particleboard Using Hydrogen Peroxide, Lignosulfonates, and Furfuryl Alcohol: Effects of Chemical Composition of Bonding Materials, J.L. Philippou, E. Zavarin, W.E. Johns, and T. Nguyen, 5:55-61 (No. 6268).

Bonding of Particleboard Using Hydrogen Peroxide, Lignosulfonates, and Furfuryl Alcohol: The Effect of Process Parameters, J.L. Philippou, W.E. Johns, E. Zavarin, and T. Nguyen, 3:27-32 (No. 6269).

Creep of Thick Structural Flakeboards in Constant and Cyclic Humidity, J.D. McNatt and M.O. Hunt, 5:49-54 (No. 6320).

Dimensional Stability of Flakeboards as Affected by Board Specific Gravity and Flake Alignment, R.L. Geimer, 8:44-52 (No. 6390).

Influence of ACA and CCA Waterborne Preservatives on the Properties of Aspen Waferboard, K. Boggio and R. Gertjejansen, 3:22-26 (No. 6316).

Influence of Paper Birch on the Properties of Aspen Waferboard: A Mill Trial, R. Gertjejansen and D. Hedquist, 11/12:33-34 (No. 6378).

Isocyanate Bonded Aspen Flakeboard, W.E. Johns, 11/12:47-50 (No. 6372).

Preservative Treatment Effects on Mechanical and Thickness Swelling Properties of Aspen Waferboard, H.J. Hall, R.O. Gertjejansen, E.L. Schmidt, C.G. Carll, and R.C. DeGroot, 11/12:19-26 (No. 6364).

Properties of Particle- and Hardboard Made From Healthy and Beetle-Killed Southern Pine, M.W. Kelly, J.E. Barefoot, W.H. Swint, and M.P. Levi, 3:33-39 (No. 6291).

U.S. Wood-Based Panel Industry: Energy, Environmental Protection, and Occupational Safety and Health, C.G. Carll, J.A. Youngquist, and H.E. Dickerhoof, 9:14-22 (No. 6344).

U.S. Wood-Based Panel Industry: Research and Technological Innovations, J.A. Youngquist, C.G. Carll, and H.E. Dickerhoof, 8:14-24 (No. 6343).

U.S. Wood-Based Panel Industry: Standards for Panel Products, C.G. Carll, H.E. Dickerhoof, and J.A. Youngquist, 7:12-15 (No. 6342).

Urethane Bonded Particleboard, J.A. Gallagher, 4:26-33 (No. 6259).

Waferboard Press Closing Strategies, D.C. Smith, 3:40-45 (No. 6183).

Residential & Commercial Buildings

Effect of Construction Variables on Performance of Wood-Stud Walls, A. Polensek, 5:37-41 (No. 6333).

Effect of Wood on Humidity in Homes, H. Kubler, 6:47-50 (No. 6393).

Methodology to Evaluate Racking Resistance of Nailed Walls, R.Y. Itani, R.L. Tuomi, and W.J. McCutcheon, 1:30-36 (No. 6205).

Moisture Movement and Control in Light-Frame Structures, G.E. Sherwood and A. TenWolde, 10:69-73 (No. 6448).

Wood-Stud Walls: Stiffness of Joints Between Studs and Hardwood Paneling, A. Polensek and K.M. Bastendorff, 7:51-53 (No. 6358).

Wood-Stud Walls: Structural Properties of Stuccoed Sheathing, A. Polensek and K.M. Bastendorff, 4:54-56 (No. 6310).

Softwood Lumber

Balsam Fir— A Potential New Source of Softwood Lumber, J.L. Bowyer, S.A. Sinclair, P.V. Sibal, and R.L. Govett, 1:53-58 (No. 6287).
Estimating Sawlog Center of Gravity by Empirical Formula, R.H. Perkins, 3:50-53 (No. 6273).
Kiln-Drying Douglas-fir Pole Sections: Effects on Strength and Checking, C.J. Kozlik, 6:24-30 (No. 6353).
Longitudinal Stress Waves for Lumber Stress Grading: Factors Affecting Applications: State of the Art, C.C. Gerhards, 2:20-25 (No. 6336).
Mold and Sapstain Control: Laboratory and Field Tests of 44 Fungicidal Formulations, A.J. Cserjesi and E.L. Johnson, 10:59-68 (No. 6354).
Regional Price Variation of Southern Pine Sawtimber and Pulpwood, T.P. Hunter, 9:23-26 (No. 6412).
Reverse Proofloading of Lumber, L.A. Marin and F.E. Woeste, 10:53-55 (No. 6294).

Treated Wood Products

Double Application of Paraquat for Production of Lightwood With High Oleoresin Content, D.R. Roberts, I.L. Williams, and S.V. Kossuth, 10:74-78 (No. 6383).
Durability of CCA-B Treated Plywood Having Nonconforming Penetration Patterns, G.B. Fahlstrom, 2:51-52 (No. 6260).
Effect of Calcium Silicate Substrate on Thermal Barrier Fire Testing, R.H. White, 7:25-27 (No. 6429).
Formaldehyde Dynamic Air Contamination by Hardwood Plywood: Effects of Several Variables and Board Treatments, G.E. Myers, 4:20-25 (No. 6373).
Health Hazards Caused by Fungi in Stored Wood Chips, T. Thornqvist and H. Lundstrom, 11/12:29-32 (No. 6369).
Industrial Use of Wood-Polymer Materials: State of the Art, J.A. Meyer, 1:24-29 (No. 6321).
Influence of ACA and CCA Waterborne Preservatives on the Properties of Aspen Waferboard, K. Boggio and R. Gertjejansen, 3:22-26 (No. 6316).
Methyl Bromide Treatment of Oak Wilt Infected Logs: Laboratory and Preliminary Field Fumigations, E.L. Schmidt, M.M. Ruetze, and D.W. French, 3:46-49 (No. 6257).
Mold and Sapstain Control: Laboratory and Field Tests of 44 Fungicidal Formulations, A.J. Cserjesi and E.L. Johnson, 10:59-68 (No. 6354).
Movement and Persistence of Chloropicrin Fumigant in Western Redcedar Poles, T.C. Scheffer, R. Inwards, and R.D. Graham, 5:33-36 (No. 6348).
Preservative Treatment Effects on Mechanical and Thickness Swelling Properties of Aspen Waferboard, H.J. Hall, R.O. Gertjejansen, E.L. Schmidt, C.G. Carll, and R.C. DeGroot, 11/12:19-26 (No. 6364).
Strength of Untreated Douglas-fir Foundation Piles After Some 70 Years' Service, A.P. Schniewind, B. Gammon, and B.A. Bendtsen, 11/12:39-46 (No. 6419).
Using Fumigants to Control Interior Decay in Waterfront Timbers, T.L. Highley and W.E. Eslyn, 2:32-34 (No. 6275).

AUTHOR INDEX

A

Andersen, A.W., see Steiner, P.R.

B

Barefoot, J.E., see Kelly, M.W.
Barton, D.J., see Chen, P.Y.S.
Bastendorff, K.M., see Polensek, A.
Bastendorff, K.M., see Polensek, A.
Beaudoin, M., R.J. Thomas, and J.G. Schroeder, Influence of Edging Practices on Furniture Dimension Stock Yields From Short Hardwood Lumber, 2:53-59 (No. 6235).
Bentley, W.R., see Brown, G.W.
Bendtsen, B.A., see Schniewind, A.P.
Biblis, E.J., W.-L. Chen, and W.-C. Lee, Rolling Shear Properties of Southern Pine Plywood and Unidirectionally Laminated Veneer, 2:45-50 (No. 6222).
Boggio, K., and R. Gertjejansen, Influence of ACA and CCA Waterborne Preservatives on the Properties of Aspen Waferboard, 3:22-26 (No. 6316).
Bonac, T., see Kirbach, E.
Bonac, T., see Kirbach, E.
Bones, J.T., Quantifying Logging Residue— Before the Fact, 6:51-52 (No. 6415).
Boone, R.S., see James, W.L.
Boone, R.S., see James, W.L.
Bowyer, J.L., S.A. Sinclair, P.V. Sibal, and R.L. Govett, Balsam Fir— A Potential New Source of Softwood Lumber, 1:53-58 (No. 6287).
Bradley, D.P., C.C. Hassler, and R.F. Green, Analytical Procedure to Locate Trees for Tree Harvest Simulators, 7:36-40 (No. 6356).
Brown, G.W., W.R. Bentley, and J.C. Gordon, Developing Harvesting Systems for the Future: Linking Strategies, Biology, and Design, 6:35-38 (No. 6384).

C

Carll, C.G., H.E. Dickerhoof, and J.A. Youngquist, U.S. Wood-Based Panel Industry: Standards for Panel Products, 7:12-15 (No. 6342).
Carll, C.G., J.A. Youngquist, and H.E. Dickerhoof, U.S. Wood-Based Panel Industry: Energy, Environmental Protection, and Occupational Safety and Health, 9:14-22 (No. 6344).
Carll, C.G., see Dickerhoof, H.E.
Carll, C.G., see Hall, H.J.
Carll, C.G., see Youngquist, J.A.

Chen, C.M., Copolymer Resins of Bark and Agricultural Residue Extracts With Phenol and Formaldehyde: 40 Percent Weight of Phenol Replacement, 11/12:14-18 (No. 6416).
Chen, C.M., Copolymer Resins of Bark and Agricultural Residue Extracts With Phenol and Formaldehyde: 20 Percent Weight of Phenol Replacement, 2:35-40 (No. 6207).
Chen, P.Y.S., and W.A. Helmer, Principles of Dehumidification Lumber Drying, 5:24-28 (No. 6329).
Chen, P.Y.S., W.A. Helmer, H.N. Rosen, and D.J. Barton, Experimental Solar-Dehumidifier Kiln for Drying Lumber, 9:35-41 (No. 6395).
Chen, W.-L., see Biblis, E.J.
Corder, S.E., see Masters, K.
Cserjesi, A.J., and E.L. Johnson, Mold and Sapstain Control: Laboratory and Field Tests of 44 Fungicidal Formulations, 10:59-68 (No. 6354).
Cubbage, F.W., and J.E. Granskog, Harvesting Systems and Costs for Southern Pine in the 1980s, 4:37-43 (No. 6317).

D

DeGroot, R.C., see Hall, H.J.
Denig, J., and E.M. Wengert, Estimating Air-Drying Moisture Content Losses for Red Oak and Yellow-poplar Lumber, 2:26-31 (No. 6280).
Dickerhoof, H.E., J.A. Youngquist, and C.G. Carll, U.S. Wood-Based Panel Industry: Production Trends and Changing Markets, 6:14-23 (No. 6341).
Dickerhoof, H.E., see Carll, C.G.
Dickerhoof, H.E., see Carll, C.G.
Dickerhoof, H.E., see Youngquist, J.A.
Dost, W.A., see Kent, M.

E

Eslyn, W.E., see Highley, T.L.

F

Fahlstrom, G.B., Durability of CCA-B Treated Plywood Having Non-conforming Penetration Patterns, 2:51-52 (No. 6260).
French, D.W., see Schmidt, E.L.

G

Gallagher, J.A., Urethane Bonded Particleboard, 4:26-33 (No. 6259).
Galligan, W.L., see James, W.L.
Gammon, B., see Schniewind, A.P.
Geimer, R.L., Dimensional Stability of Flakeboards as Affected by Board Specific Gravity and Flake Alignment, 8:44-52 (No. 6390).
Geimer, R.L., G.H. Stevens, and R.E. Kinney, Automation of a Laboratory Particleboard Press, 4:34-36 (No. 6382).
Gerhards, C.C., Longitudinal Stress Waves for Lumber Stress Grading: Factors Affecting Applications: State of the Art, 2:20-25 (No. 6336).
Gertjejansen, R., and D. Hedquist, Influence of Paper Birch on the Properties of Aspen Waferboard: A Mill Trial, 11/12:33-34 (No. 6378).
Gertjejansen, R., see Bossio, K.
Gertjejansen, R.O., see Hall, H.J.
Gordon, J.C., see Brown, G.W.
Govett, R.L., see Bowyer, J.L.
Graham, R.D., see Scheffer, T.C.
Granskog, J.E., see Cubbage, F.W.
Green, R.F., see Bradley, D.P.

H

Hall, H.J., R.O. Gertjejansen, E.L. Schmidt, C.G. Carll, and R.C. DeGroot, Preservative Treatment Effects on Mechanical and Thickness Swelling Properties of Aspen Waferboard, 11/12:19-26 (No. 6364).
Harris, R.A., Market Potential for Wood Fuel—A Limiting Factor in Wood Energy Development, 11/12: 67-70 (No. 6394).
Harris, R.A., Rapid Determination of Wood Fuel Moisture Content Using a Microwave Oven for Drying, 10:56-58 (No. 6441).
Hassler, C.C., see Bradley, D.P.
Havgreen, J.G., Mechanics of Compression Drying Solid Wood Cubes and Chip Mats, 10:30-38 (No. 6446).
Hedquist, D., see Gertjejansen, R.
Helmer, W.A., see Chen, P.Y.S.
Helmer, W.A., see Chen, P.Y.S.
Herrick, O.W., Estimating Benefits From Whole-Tree Chipping as a Logging Innovation in Northern U.S. Forests, 11/12:57-60 (No. 6449).
Highley, T.L., and W.E. Eslyn, Using Fumigants to Control Interior Decay in Waterfront Timbers, 2:32-34 (No. 6275).
Holland, J.S., see McLain, T.E.
Huber, H.A., C.W. McMillin, and A. Rasher, Economics of Cutting Wood Parts With a Laser Under Optical Image Analyzer Control, 3:16-21 (No. 6299).
Huber, H.A., see Stewart, H.A.
Hunt, M.O., see McNatt, J.D.
Hunter, T.P., Regional Price Variation of Southern Pine Sawtimber and Pulpwood, 9:23-26 (No. 6412).

I

Ince, P.J., Economic Perspective on Harvesting and Physical Constraints on Utilizing Small, Dead Lodgepole Pine, 11/12:61-66 (No. 6434).
Inwards, R., see Scheffer, T.C.
Itani, R.Y., R.L. Tuomi, and W.J. McCutcheon, Methodology to Evaluate Racking Resistance of Nailed Walls, 1:30-36 (No. 6205).

J

James, W.L., and R.S. Boone, Some General Characteristics of Capacitive In-Kiln Moisture Monitors, 4:57 (No. 6399).
James, W.L., R.S. Boone, and W.L. Galligan, Using Speed of Sound in Wood to Monitor Drying in a Kiln, 9:27-34 (No. 6401).
Jansson, M.B., Hardboard Quality When Produced in Closed White

Water Systems, 6:39-46 (No. 6309).
Jape, A.D., and T.F. McGowan, Construction and Startup of a Wood Gasification Pilot Plant, 7:45-50 (No. 6355).
Johns, W.E., Isocyanate Bonded Aspen Flakeboard, 11/12:47-50 (No. 6372).
Johns, W.E., see Philippou, J.L.
Johns, W.E., see Philippou, J.L.
Johnson, E.L., see Cserjesi, A.J.
Jung, J., Properties of Parallel-Laminated Veneer From Stress-Wave-Tested Veneers, 7:30-35 (No. 6380).

K

Kaiser, H.F., see Risbrudt, C.D.
Kelly, M.W., J.E. Barefoot, W.H. Swint, and M.P. Levi, Properties of Particle- and Hardboard Made From Healthy and Beetle-Killed Southern Pine, 3:33-39 (No. 6291).
Kent, M., J.A. Wagar, and W.A. Dost, Economic Feasibility of Utilizing Urban Wood: Case Study of the San Francisco Bay Area, 9:46-52 (No. 6338).
Kersavage, P.C., see Savsar, M.
Kinney, R.E., see Geimer, R.L.
Kirbach, E., and T. Bonac, Alloy Tipping for Reduced Sawtooth Dulling, 8:36-40 (No. 6295).
Kirbach, E., and T. Bonac, Dulling of Sawteeth Tipped With a Stellite and Two Cobalt-Cemented Tungsten Carbides, 9:42-45 (No. 6252).
Kossuth, S.V., see Roberts, D.R.
Kozlik, C.J., Kiln-Drying Douglas-fir Pole Sections: Effects on Strength and Checking, 6:24-30 (No. 6353).
Kubler, H., Effect of Wood on Humidity in Homes, 6:47-50 (No. 6393).

L

Laufenberg, T., Exposure Effects Upon Performance of Laminated Veneer Lumber and Glulam Materials, 5:42-48 (No. 6330).
Leatham, G.F., Cultivation of Shiitake, the Japanese Forest Mushroom, on Logs: A Potential Industry for the United States, 8:29-35 (No. 6350).
Lee, W.-C., see Biblis, E.J.
Levi, M.P., see Kelly, M.W.
Lundstrom, H., see Thornqvist, T.

M

Marin, L.A., and F.E. Woeste, Reverse Proofloading of Lumber, 10:53-55 (No. 6294).
Marx, C.M., and R.C. Moody, Effect of Lumber Width and Tension Lamination Quality on the Bending Strength of Four-Ply Laminated Beams, 1:45-52 (No. 6254).
Masters, K., and S.E. Corder, Steam Recovery in a High-Temperature Lumber Dry Kiln by Steam-Jet Thermocompressor, 4:50-53 (No. 6139).
Max, T.A., and T.A. Snellgrove, Selecting Precision Levels for Measurements, 11/12:27-28 (No. 6475).
McCutcheon, W.J., see Itani, R.Y.
McGowan, T.F., see Jape, A.D.
McLain, T.E., and J.S. Holland, Preliminary Evaluation of the Strength and Stiffness of Yellow-poplar Pallet Shook, 11/12:51-56 (No. 6418).
McMillin, C.W., see Huber, H.A.
McNatt, J.D., and M.O. Hunt, Creep of Thick Structural Flakeboards in Constant and Cyclic Humidity, 5:49-54 (No. 6320).
Meyer, J.A., Industrial Use of Wood-Polymer Materials: State of the Art, 1:24-29 (No. 6321).
Miller, D.J., Wood Lath Filters in Waste-Water Treatment Plants, 2:41-44 (No. 6276).
Mills, W.L., Jr., see Tufts, R.A.
Moody, R.C., see Marx, C.M.
Myers, G.C., Response of Experimental Hardboard Dimensions and Weight to Cyclic Relative Humidity, 7:41-44 (No. 6392).
Myers, G.E., Formaldehyde Dynamic Air Contamination by Hardwood Plywood: Effects of Several Variables and Board Treatments, 4:20-25 (No. 6373).

N

Nguyen, T., see Philippou, J.L.
Nguyen, T., see Philippou, J.L.

O

Oliveira, L.C. de S., C. Skaar, and E.M. Wengert, Solar and Air Lumber Drying During Winter in Virginia, 1:37-44 (No. 6256).

P

Perkins, R.H., Estimating Sawlog Center of Gravity by Empirical Formula, 3:50-53 (No. 6273).
Perkins, R.H., Procedure for Calculating Distributed Load Deflection in Log Beams, 8:41-43 (No. 6411).
Philippou, J.L., W.E. Johns, E. Zavarin, and T. Nguyen, Bonding of Particleboard Using Hydrogen Peroxide, Lignosulfonates, and Furfuryl Alcohol: The Effect of Process Parameters, 3:27-32 (No. 6269).
Philippou, J.L., E. Zavarin, W.E. Johns, and T. Nguyen, Bonding of Particleboard Using Hydrogen Peroxide, Lignosulfonates, and Furfuryl Alcohol: Effects of Chemical Composition of Bonding Materials, 5:55-61 (No. 6268).
Polensek, A., Effect of Construction Variables on Performance of Wood-Stud Walls, 5:37-41 (No. 6333).
Polensek, A., and K.M. Bastendorff, Wood-Stud Walls: Stiffness of Joints Between Studs and Hardwood Paneling, 7:51-53 (No. 6358).
Polensek, A., and K.M. Bastendorff, Wood-Stud Walls: Structural Properties of Stuccoed Sheathing, 4:54-56 (No. 6310).

R

Rasher, A., see Huber, H.A.
Rasher, A.A., see Stewart, H.A.
Risbrudt, C.D., and H.F. Kaiser, Economic Analysis of the Sawmill Improvement Program, 8:25-28 (No. 6362).
Roberts, D.R., I.L. Williams, and

S.V. Kossuth, Double Application of Paraquat for Production of Lightwood With High Oleoresin Content, 10:74-78 (No. 6383).
Rosen, H.N., see Chen, P.Y.S.
Rosen, H.N., see Stewart, H.A.
Ruetze, M.M., see Schmidt, E.L.
Rusch, J.J., see Zoch, L.L., Jr.

S

Savsar, M., and P.C. Kersavage, Mathematical Model for Determining the Quantity of Materials Produced in Sawmilling, 11/12:35-38 (No. 6458).
Scheffer, T.C., R. Inwards, and R.D. Graham, Movement and Persistence of Chloropicrin Fumigant in Western Redcedar Poles, 5:33-36 (No. 6348).
Schmidt, E.L., M.M Ruetze, and D.W. French, Methyl Bromide Treatment of Oak Wilt Infected Logs: Laboratory and Preliminary Field Fumigations, 3:46-49 (No. 6257).
Schmidt, E.L., see Hall, H.J.
Schniewind, A.P., B. Gammon, and B.A. Bendtsen, Strength of Untreated Douglas-fir Foundation Piles After Some 70 Years' Service, 11/12:39-46 (No. 6419).
Schroeder, J.G., see Beaudoin, M.
Sherwood, G.E., and A. TenWolde, Moisture Movement and Control in Light-Frame Structures, 10:69-73 (No. 6448).
Sibal, P.V., see Bowyer, J.L.
Simpson, W., Warp Reduction in Kiln-Drying Hardwood Dimension, 5:29-32 (No. 6308).
Simpson, W.T., Predrying Before Press-Drying to Reduce Drying Defects in Hardwoods, 11/12:77-80 (No. 6428).
Sinclair, S.A., see Bowyer, J.L.
Sirois, D.L., see Smith, L.A.
Skaar, C., see Oliveira, L.C. de S.
Sliker, A., and O. Suchsland, Examination of a Sinusoidal Joint for Assembling Wood I-Beam Components, 7:16-20 (No. 6335).
Smith, D.C., Waferboard Press Closing Strategies, 3:40-45 (No. 6183).
Smith, L.A., and D.L. Sirois, Ergonomic Research: Review and Needs in Southern Forest Harvesting, 4:44-49 (No. 6345).
Snellgrove, T.A., see Max, T.A.
Springer, E.L., see Zoch, L.L., Jr.
Steiner, P.R., and A.W. Andersen, Effects of Veneer Preheating Temperature, Press and Assembly Time on Aspen LVL, 10:39-44 (No. 6346).
Stevens, G.H., see Geimer, R.L.
Stewart, H.A., H.N. Rosen, H.A. Huber, and A.A. Rasher, 4/4 Hardwood Dimension From Short Bolts: Economic and Processing Comparison of Conventional and Innovative Production, 11/12:71-76 (No. 6409).
Suchsland, O., see Sliker, A.
Swint, W.H., see Kelly, M.W.

T

TenWolde, A., see Sherwood, G.E.
Thomas, R.J., see Beaudoin, M.
Thornqvist, T., and H. Lundstrom, Health Hazards Caused by Fungi in Stored Wood Chips, 11/12:29-32 (No. 6369).
Tufts, R.A., and W.L. Mills, Jr., Financial Analysis of Equipment Replacement, 10:45-52 (No. 6406).
Tuomi, R.L., see Itani, R.Y.

V

Vidrine, C.G., and G.E. Woodson, Bulk Densities of Materials From Selected Pine-Site Hardwoods, 7:21-24 (No. 6245).

W

Wagar, J.A., see Kent, M.
Wengert, E.M., see Denig, J.
Wengert, E.M., see Oliveira, L.C. de S.
White, R.H., Effect of Calcium Silicate Substrate on Thermal Barrier Fire Testing, 7:25-27 (No. 6429).
Williams, I.L., see Roberts, D.R.
Woodson, G.E., see Vidrine, C.G.
Woeste, F.E., see Marin, L.A.

Y

Youngquist, J.A., C.G. Carll, and H.E. Dickerhoof, U.S. Wood-Based Panel Industry: Research and Technological Innovations, 8:14-24 (No. 6343).
Youngquist, J.A., see Carll, C.G.
Youngquist, J.A., see Carll, C.G.
Youngquist, J.A., see Dickerhoof, H.E.

Z

Zavarin, E., see Philippou, J.L.
Zavarin, E., see Philippou, J.L.
Zoch, L.L., Jr., J.J. Rusch, and E.L. Springer, Changes in Aspen Bark Stored in Outdoor Piles, 6:31-34 (No. 6376).